

# SPECIFICATIONS

## Pump Kit on S 28 X

## 2023-4 130/80 SC

	U.S. Rod/Piston	Metric Rod/Piston
Theor. Concrete Output Per Hour (cubic yards - cubic meters)	151/95	115/73
Maximum Pressure on Concrete (psi - bar)	863/1389	60/96
Maximum Strokes Per Minute	23/15	23/15
Pump Cylinder Diameter (in. - mm)	9	230
Pump Cylinder Stroke Length (in. - mm)	79	2000
Differential Cylinder Size (in. - mm)	5.1	130
Maximum Aggregate Size (in. - mm)	2.5	63.5

## Boom Specifications

	U.S.	Metric
Pipeline Diameter (in. - mm)	5	125
Vertical Reach (ft. - m)	91	28
Horizontal Reach (ft.-in. - m)	77'-7"	23.6
Net Horizontal Reach (ft.-in. - m)	70'-5"	21.4
Unfolding Height (ft.-in. - m)	19'-2"	5.8
<b>Section Lengths</b>		
First Section (ft.-in. - m)	23'-3"	7
Second Section (ft.-in. - m)	18'-1"	5.5
Third Section (ft.-in. - m)	18'-1"	5.5
Fourth Section (ft.-in. - m)	18'-1"	5.5
Slewing Range (degrees)	370°	370°
End hose length (ft. - m)	12	3.7

Specifications are subject to change without prior notice.

